## THE 2.3M120

## **OPTIMIZED FOR MEDIUM WIND SEGMENT**



## The Senvion 2.XM Series

Our new 2MW+ series wind turbine generator with a hub height of 120m has been optimized for higher yields at medium – low wind site. With an operating temperature range of upto 40 °C, it can also be operated in tropical climates. The supply chain is localized. The 2.XM series is fully compliant with Indian grid code requirement.

Design Data	
Nominal Power (kW)	2300
Cut in wind speed (m/s)	3.0
Cut out wind speed (m/s)	20.0
Nominal wind speed (m/s)	11.0
Operating Temperature range (°C)	-10 to 40
Survival Temperature range (°C)	-20 to 50

Rotor	
Diameter (m)	120.0
Rotor Area (m2)	11,310
Power Control	Electrical pitch system


Certification			
Hub	Wind Class	DIBt	T
——————————————————————————————————————	VVIIIU CIdSS	wind zone	Transformer
120	IEC S (based on IIIB)	-	ETS

Tower	
Max. sound power level (dB[A])	107.0

Electrical System		`	
	Nominal Frequency (Hz)	50	
	Converter Type	Converter (Full power conversion)	
	Generator	Electrically excited synchronous generator	
	Generator protection class	IP 54	

Rotor Blade	
Length (m)	LM 58.7
Туре	GFRP

## **Power Curve**









Scan the QR code and download the brochure.